


ohla sofa

design Alberto Brogliato



STRUTTURA/STRUCTURE



GROSS WEIGHT:

6304 kg 34,2
6575 kg 37,4


ACCESSORIES:

A4668
Sistema di fissaggio
a terra (2 kit)/
Ground fixing kit (2 kit)

A4601
Kit sabbia essiccata/
Dried sand kit


PE - Polietilene/Polyethylene
colore base/basic colour

6304



PE - Polietilene/Polyethylene
laccati/lacquered

6575



TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability
and safety, 1st level EN 16139:2013

Tests carried out as per:
EN 16139:2013 + AC:2013
EN 1728:2012 + AC:2013
EN 1022:2005

Conforms to the mechanical and structural safety
requirements of ANSI BIFMA X5.4-2012

Tests carried out as per:
ANSI-BIFMA X5.4-2012/7
ANSI-BIFMA X5.4-2012/5
ANSI-BIFMA X5.4-2012/8
ANSI-BIFMA X5.4-2012/6
ANSI-BIFMA X5.4-2012/14
ANSI-BIFMA X5.4-2012/12
ANSI-BIFMA X5.4-2012/15
ANSI-BIFMA X5.4-2012/9
ANSI-BIFMA X5.4-2012/10
ANSI-BIFMA X5.4-2012/11
ANSI-BIFMA X5.4-2012/16
ANSI-BIFMA X5.4-2012/17
ANSI-BIFMA X5.4-2012/21


ohla sofa light

design Alberto Brogliato



STRUTTURA/STRUCTURE

PE - Polietilene/Polyethylene
colore base/basic colour



8304

98

GROSS WEIGHT:

kg 34,2

ACCESSORIES:

A4668

Sistema di fissaggio
a terra (2 kit)/
Ground fixing kit (2 kit)

Necessita di 2 Kit Luce/
Needs 2 Light Kit

TESTS

Declarations of conformity issued by **CATAS**

Conforms to the requirements of resistance, durability
and safety, 1st level EN 16139:2013

Tests carried out as per:

EN 16139:2013 + AC:2013

EN 1728:2012 + AC:2013

EN 1022:2005

Conforms to the mechanical and structural safety
requirements of ANSI BIFMA X5.4-2012

Tests carried out as per:

ANSI-BIFMA X5.4-2012/7

ANSI-BIFMA X5.4-2012/5

ANSI-BIFMA X5.4-2012/8

ANSI-BIFMA X5.4-2012/6

ANSI-BIFMA X5.4-2012/14

ANSI-BIFMA X5.4-2012/12

ANSI-BIFMA X5.4-2012/15

ANSI-BIFMA X5.4-2012/9

ANSI-BIFMA X5.4-2012/10

ANSI-BIFMA X5.4-2012/11

ANSI-BIFMA X5.4-2012/16

ANSI-BIFMA X5.4-2012/17

ANSI-BIFMA X5.4-2012/21

KIT LUCE/LIGHT KIT

A4183 - indoor



dettagli/details

Cavo trasparente/
Transparent cable

Pulsantiera a pedale/
Foot switch

Spina europea bipolare/
European bipolar plug

Lunghezza cavo 370 cm/
Wire length 370 cm

Predisposizione per
base di stabilizzazione/
Arrangement for stability base

LUCE/LIGHT 1 x 20 W



A4182 - outdoor



dettagli/details

Guscio in policarbonato/
Polycarbonate shell

Guarnizione a tenuta/
Gasket seal

Cavo nero/
Black cable

Spina Schuko antispruzzo/
Anti-splash Schuko plug

Lunghezza cavo 280 cm/
Wire length 280 cm

Predisposizione per
base di stabilizzazione/
Arrangement for stability base

LUCE/LIGHT 1 x 20 W

